

Multi Media Converter



MMC-1000

Analog to SDI



ATS-500

Introduction

Composite, Component, HDMI, HD-SDI 등 다양한 입력신호를 수신하여 스위칭을 통하여 선택한 신호를 HDMI, HD-SDI 신호로 동시에 출력하는 고성능 Multi Media Converter입니다.

Feature

- Inputs : HDMI, HD-SDI, Component, Composite
- Outputs : HDMI, HD-SDI
- AES/EBU(BNC), Analog L/R Audio Input Interface
- HDMI, 3G/HD/SD-SDI Supports
- HDMI v1.3 Standards Support
- HDMI/SDI Dual Output
- 2Ch Mini XLR Audio Inputs Interface

Specifications

Video Input

Input	Input	Composite, Component
Analog	Input	HDMI, 3G/SD/HD-SDI
Digital	Input	480i(29.9/30), 576i(25), 720p(59.94/60)
Resolutions		1080i(25/29.97/30)
		1080p(23.98/24/25/29.97/30/50/59.94/60)
Impedance		75 Ω
Aspect Ratio		4:3, 16:9

Audio Input

Input	Input	Stereo
Analog	Input	20 Hz~20 KHz
	Freq. Range	600 Ω/20k Ω
	Impedance	Mini XLR
	Connector	Input
Digital	Input	AES/EBU, Embedded HDMI/SDI
	Sampling Rate	32, 44.1 & 48 KHz
	Connector	HDMI-19PIN, BNC(75 Ω)

SDI Output

Output	Output	SMPTE-259/272/274/292/296/299/424
Compliance		SD-SDI : 270 Mbps
Data Rates		HD-SDI : 1.5 Gb/s & 3 Gb/s
Video Rates		4:2:2
Color Space		YUV

HDMI Output

Output	Output	4:2:2, 4:4:4, RGB
Color Precision		

Video Output

Output	Output	HDMI, HD-SDI & 3Gb/s SDI
Digital		
Impedance		75 Ω
Aspect Ratio		4:3, 16:9

General

General	General	DC 12 V
Power Requirements		13 W
Power Consumption		0.74 Kg
Weight		270 x 170 x 35 mm
Dimensions(WxDxH)		

Introduction

Composite, Component Analog 입력신호를 수신하여 Digital Format HD-SDI로 변환 출력하는 고품질 Analog to HD-SDI Media Converter입니다.

Feature

- Input : Component, Composite, Analog L/R Audio Input
- Output : HD/SD-SDI
- Upload and Configuration via USB2.0

Specifications

Video Input

Input	Input	Composite, Component
Analog	Input	480i(29.9/30), 576i(25)
Resolutions		720p(50/59.94/60), 1080i(25/29.97/30)
Impedance		75 Ω
Aspect Ratio		4:3, 16:9

Audio Input

Input	Input	Stereo
Analog	Input	20 Hz~20 KHz
	Freq. Range	600 Ω/20 kΩ
	Impedance	6.35mm Phone Jack
	Connector	

Video Output

Output	Output	HD/HD-SDI 2 Port
Digital		75 Ω
Impedance		4:3, 16:9
Aspect Ratio		SMPTE-259/272/274/292/296/299
Compliance		SD-SDI : 270 Mbps
Data Rates		HD-SDI : 1.5 Gb/s
Video Rates		4:2:2
Color Space		YUV

General

General	General	DC 12 V
Power Requirements		230 g
Weight		110 x 90 x 28 mm
Dimensions(WxDxH)		